



This Liotta Modular Light is the perfect choice. The concept of innovation with a good performance, uniqueness, durability and versatility. 350° horizontal rotation, 25° rotation from the left to the right, accurate adjusted angle. The antiglare effect is the warranty of a bright, homogeneous, comfortable light result. Regular shape and two clips make retrofit installation quick and easy. The option to choose between single or double combination ensures various light directions and beam effects. The high efficiency of the LED source ensures high performances and low consumptions and emitted bright and pleasant. The possible applications are Shopping Malls, Retailer, Home, fashion markets etc.

HOUSING: Die cast aluminium

REFLECTOR: Anodized Aluminium

LED: Reducy Energy Consumption with L80/B10/F10

AVERAGE LIFE: 50,000 hrs Lifetime Working Under Temp (-20°C - 50°C)

Technical Specifications

Item Code	Power	Lumen	Dimension	Hole
PLL852010	10W	1200lm	86x155x105h	86x86
PLL852015	15W	1800lm	125x197x140h	126x126
PLL852020	20W	2400lm	125x197x140h	126x126
PLL852030	30W	3600lm	125x197x140h	126x126
PLL853020	20W	2400lm	85x237x135h	82x162
PLL853030	30W	3600lm	125x317x175h	126x146
PLL853040	40W	4800lm	125x317x175h	126x146
PLL853060	60W	7200lm	125x317x175h	126x146
PLL854030	30W	3600lm	85x315x135h	86x245
PLL854045	45W	5400lm	125x427x175h	126x356
PLL854060	60W	7200lm	125x427x175h	126x356
PLL854090	90W	10800lm	125x427x175h	126x356

Technical Drawings

